



**PRODUCT DATA SHEET**

Date: 05/13/2024

**Spinnaker**  
 550 Summit Avenue  
 Troy, Oh 45373  
 800 543-9452

**2.4m White Pearlized BOPP \*\* VG-325 \*\* 1.2 mil Clear Polyester**

Item#: 0048992

----- TRIMLESS PROGRAMS -----

Dist. Ctr	Length	Min. Width	Core
Chicago	2.5 K	3"	3"
Chicago	5 K	3"	3"
Chicago	10 K	4"	3"
Ontario, CA	2.5 K	3"	3"
Ontario, CA	5 K	3"	3"
Ontario, CA	10 K	4"	3"

Facestock: **2.4m White Pearlized BOPP**

A top coated white polypropylene film with a pearlized appearance. This product offers excellent flexo printability. We have also had success with thermal transfer printing using resin and wax/resin ribbons. Testing is recommended with your specific printer and ribbon combinations. This component is not available for custom constructions.

Basis Weight:  
 Caliper:  
 Gloss:  
 Opacity:

**Typical Value**  
 30 #/3300 ft<sup>2</sup>  
 2.4 mils  
 95 / N/A%  
 89%

Adhesive: **VG-325**

A general purpose permanent emulsion acrylic adhesive that offers excellent adhesion. This component is not available for custom constructions.

Coat Weight:  
 Coat Weight:  
 Caliper:  
 Adhesion to Stainless Steel, oz. (90° Peel):  
 Loop Tack, oz.:  
 Service Temperature:  
 Minimum Application Temperature:

**Typical Value**  
 13.5 #/3300 ft<sup>2</sup>  
 19.98 grams/m<sup>2</sup>  
 .4 mils  
 33  
 39  
 -40 to 248 °F  
 25 °F

---

**Release Liner: 1.2 mil Clear Polyester**

A 1.2 mil clear polyester liner is designed for roll label applications where smoothness, cleanliness, aesthetics and the strength properties of the liner are emphasized. This liner is coated with a premium release system designed for the reliable dispensing of film products. This component is not available for custom constructions.

Basis Weight:

**Typical Value**

28.3 #/3000 ft<sup>2</sup>

Caliper:

1.18 mils

Tensile MD/CD:

22,700 / 19,900 #/inch

**Total Product Caliper:** 3.98 mils

*For application recommendations call 877-210-5104*

**Product Basis Weight Per MMSI:** 157.12 #

*For samples or other questions please call your Sales Representative.*

**Shelf Life:** 12 month(s) when stored at 72° F, 50% RH

**Important Notice**

These are typical values and should not be considered a specification. Adhesive properties were tested with a film facestock unless denoted with an asterisk(\*).

All trademarks are the property of their respective owners.

All information, recommendations for use, product designations, and descriptive materials about Spinnaker Pressure Sensitive Products, LLC products are believed to be reliable, but the furnishing of such information, recommendations for use, product designations, and descriptive material is for informational purposes only and does not constitute a warranty of any kind by Spinnaker Pressure Sensitive Products, LLC. Because of the variety of possible applications for Spinnaker's products and the continuing development of new applications, all Spinnaker Pressure Sensitive Products, LLC products are sold with the understanding that each purchaser will independently determine the suitability of any product for the purchaser's intended application, converting, and print processes. Spinnaker Pressure Sensitive Products, LLC will review, and may modify the information contained in this document from time to time and customers should ensure they have the most recent information.

Last Revision: 04/02/2024