

## PRODUCT DATA SHEET

Date: 05/13/2024

**Spinnaker** 550 Summit Avenue Troy, Oh 45373 800 543-9452

## 2.6 mil TC White Label-Lyte® \*\* VA-365 \*\* 1.2mil Clear PET Liner

]	<b>TRIML</b>	ESS P	ROGR	<b>AMS</b>	
---	--------------	-------	------	------------	--

Dist. Ctr	Length	Min. Width	Core
Chicago	2.5 K	3"	3"
Chicago	5 K	3"	3"
Chicago	10 K	4"	3"
Los Angeles	2.5 K	3"	3"
Los Angeles	5 K	3"	3"
Los Angeles	10 K	4"	3"

Facestock: **2.6 mil TC White Label-Lyte**® A white, multi-layer, biaxially-oriented polypropylene film that is

top-coated for ink receptivity.

**Typical Value** 

Basis Weight: 33.2 #/3300 ft<sup>2</sup>
Caliper: 2.6 mils

Caliper: 2.6 mils
Tensile MD/CD: 12,600 / 22,200 PSI

Elongation @ Break MD/TD: 180 / 45% Opacity: 88%

Adhesive: VA-365 An economical all-temperature acrylic adhesive choice for a wide range of

application temperatures. This component is not available for custom

constructions.

**Typical Value** 

Coat Weight:  $12.5 \#/3300 \text{ ft}^2$ Coat Weight:  $18.5 \text{ grams/m}^2$ 

Caliper: .4 mils Adhesion to Stainless Steel, oz. (90° Peel): 28 Loop Tack, oz.: 50

Service Temperature: -65 to 200 °F

Minimum Application Temperature: -20 °F

Release Liner: 1.2mil Clear PET Liner A durable 1.2 mil polyester liner suitable for high-speed diecutting and stripping

applications. Used primarily for roll-to-roll, high-speed dispensing applications

For application recommendations call 877-210-5104

For samples or other questions please call your Sales Representative.

**Typical Value** 

Basis Weight:  $26 \#/3000 \text{ ft}^2$  Caliper: 1.2 mils

**Total Product Caliper:** 4.2 mils

**Product Basis Weight Per MMSI:** 156.42 #

**Shelf Life:** 12 month(s) when stored at 72° F, 50% RH

Important Notice

These are typical values and should not be considered a specification. Adhesive properties were tested with a film facestock unless denoted with an asterisk(\*).

All trademarks are the property of their respective owners.

All information, recommendations for use, product designations, and descriptive materials about Spinnaker Pressure Sensitive Products, LLC products are believed to be reliable, but the furnishing of such information, recommendations for use, product designations, and descriptive material is for informational purposes only and does not constitute a warranty of any kind by Spinnaker Pressure Sensitive Products, LLC. Because of the variety of possible applications for Spinnaker's products and the continuing development of new applications, all Spinnaker Pressure Sensitive Products, LLC products are sold with the understanding that each purchaser will independently determine the suitability of any product for the purchaser's intended application, converting, and print processes. Spinnaker Pressure Sensitive Products, LLC will review, and may modify the information contained in this document from time to time and customers should ensure they have the most recent information.

Last Revision: 06/28/2022