

PRODUCT DATA SHEET

Date: 05/08/2025

Spinnaker

550 Summit Avenue Troy, Oh 45373 800 543-9452

SafeTETM NT Red Void Polyester ** VR ** 60# Blue

Item#: 0049946

flexography ar ear resistance,	Min. Width 3" 3" oid polyester, topcoa nd thermal transfer pr dimensional stability	inters. Features and
5 K -transferable v flexography ar ear resistance,	3" oid polyester, topcoa nd thermal transfer pr dimensional stability	3" ted for superior inters. Features and
-transferable v flexography ar ear resistance,	oid polyester, topcoa nd thermal transfer pr dimensional stability	ted for superior inters. Features and
flexography ar ear resistance,	nd thermal transfer pr dimensional stability	inters. Features and
	for your application.	ılt with your ink
ı	ι	ı

Adhesive: VR	This is unique removable acrylic that will generate the VOID letter on the film side but does not make residue on the applied surface. The performance may vary depending on the type and finish of the surface, so have prior testing before usage.
	Typical Value
Caliper:	1 mils
Adhesion to Stainless Steel, oz. (90° Peel):	12
Loop Tack, oz.:	21
Service Temperature:	14 to 176 °F
Minimum Application Temperature:	50 °F
Shear (1000g):	>10,000 minutes

Release Liner: 60# Blue

A 60# blue glassine liner. Excellent for die cutting and stripping. The liner is coated with a release system designed for label dispensing. Primarily for roll–to-roll applications where a more demanding liner is needed.

Basis Weight: Caliper: **Typical Value** 60 #/3000 ft² 3.5 mils

Total Product Caliper: 6 mils **Product Basis Weight Per MMSI:** 214.32 # **Shelf Life:** 12 month(s) when stored at 72° F, 50% RH For application recommendations call 877-210-5104 For samples or other questions please call your Sales Representative.

Important Notice

These are typical values and should not be considered a specification. Adhesive properties were tested with a film facestock unless denoted with an asterisk(*).

All trademarks are the property of their respective owners.

All information, recommendations for use, product designations, and descriptive materials about Spinnaker Pressure Sensitive Products, LLC products are believed to be reliable, but the furnishing of such information, recommendations for use, product designations, and descriptive material is for informational purposes only and does not constitute a warranty of any kind by Spinnaker Pressure Sensitive Products, LLC. Because of the variety of possible applications for Spinnaker's products and the continuing development of new applications, all Spinnaker Pressure Sensitive Products, LLC products are sold with the understanding that each purchaser will independently determine the suitability of any product for the purchaser's intended application, converting, and print processes. Spinnaker Pressure Sensitive Products, LLC will review, and may modify the information contained in this document from time to time and customers should ensure they have the most recent information.

Last Revision: 05/22/2023