

PRODUCT DATA SHEET

Date: 05/10/2024

Spinnaker 550 Summit Avenue Troy, Oh 45373 800 543-9452

Veero™ 50# Laser ** VG-LZ ** 3.2 mil Veero L.F. Liner

Item#: 0050177

TRIMLESS PROGRAMS			
Dist. Ctr	Length	Min. Width	Core
Chicago	2.5 K	3"	6"
Chicago	5 K	3"	6"
Chicago	10 K	4"	6"
Ontario, CA	2.5 K	3"	6"
Ontario, CA	5 K	3"	6"
Ontario, CA	10 K	4"	6"

Facestock: **Veero**TM **50**# **Laser** A bright white, uncoated paper designed to be compatible with

most low-speed and high-speed laser printers and many color and monochrome ink jet printers. An economical choice for laser and ink jet applications. This component is not available for custom

constructions.

Typical Value

 Basis Weight:
 50 #/3300 ft²

 Caliper:
 3.8 mils

 Tensile MD/CD:
 32 / 17 #/inch

 Tear MD/CD:
 50 / 53 grams

 Opacity:
 87%

 Parker Print:
 5.8 microns

Parker Print: 5.8 m Brightness: 92%

Adhesive: VG-LZ A general purpose, permanent acrylic emulsion adhesive designed specifically

for laser applications. This adhesive has excellent ultimate adhesion

to a wide variety of substrates.

Typical Value

Coat Weight: $11.6 \#/3300 \text{ ft}^2$ Coat Weight: 17.168 grams/m^2

Caliper: 0.7 mils Adhesion to Stainless Steel, oz. (90° Peel): 36 Loop Tack, oz.: 62

Service Temperature: -75 to 200 °F

Minimum Application Temperature: 25 °F

Shear (1000g): 70 minutes

Release Liner: 3.2 mil Veero L.F. Liner A clay coated kraft lay flat liner specially selected for use in toner fusion and

other non-impact printer roll-to-sheet applications

For application recommendations call 877-210-5104

For samples or other questions please call your Sales Representative.

Typical Value

44 #/3000 ft² Basis Weight: Caliper: 3.2 mils Tensile MD/CD: 24 / 11 #/inch Tear MD/CD: 51 / 59 grams

Opacity: 81%

Total Product Caliper: 7.7 mils **Product Basis Weight Per MMSI:** 231.58 #

Shelf Life: 12 month(s) when stored at 72° F, 50% RH

Important Notice

These are typical values and should not be considered a specification. Adhesive properties were tested with a film facestock unless denoted with an asterisk(*).

All trademarks are the property of their respective owners.

All information, recommendations for use, product designations, and descriptive materials about Spinnaker Pressure Sensitive Products, LLC products are believed to be reliable, but the furnishing of such information, recommendations for use, product designations, and descriptive material is for informational purposes only and does not constitute a warranty of any kind by Spinnaker Pressure Sensitive Products, LLC. Because of the variety of possible applications for Spinnaker's products and the continuing development of new applications, all Spinnaker Pressure Sensitive Products, LLC products are sold with the understanding that each purchaser will independently determine the suitability of any product for the purchaser's intended application, converting, and print processes. Spinnaker Pressure Sensitive Products, LLC will review, and may modify the information contained in this document from time to time and customers should ensure they have the most recent information.

Last Revision: 08/08/2023