

PCW Content:

PRODUCT DATA SHEET

Date: 05/08/2025

Spinnaker 550 Summit Avenue Troy, Oh 45373 800 543-9452

DiversiPrint® 60# Bright White ** MP376SS Permanent ** 58# 0-Split

Facestock: DiversiPrint® 60# Bright White A premium bright white offset offering excellent contrast and ink

receptivity, this uncoated sheet is designed to be compatible with most desk top, high-speed laser printers and copiers. Also suitable

for ink jet printing.

Typical Value

Basis Weight: $60 \#/3300 \text{ ft}^2$ Caliper: 4.6 mils Opacity: 92% Brightness: 98%

GSM: 202

Adhesive: MP376SS Permanent An aggressive, acrylic emulsion general-purpose permanent adhesive designed

10%

to cut cleanly while yielding excellent adhesion to a wide variety of surfaces, including corrugated and low energy surfaces. This is the standard permanent adhesive used in stocking sheet items produced with a paper facestock and

select film products

Typical Value

Caliper: .7 mils

Service Temperature: -65 to 180 °F

Minimum Application Temperature: 35 °F

Release Liner: 58# 0-Split

A liner specifically designed to meet the stringent lay flat requirements of

digital sheet print media. Combined with the appropriate face stock and adhesive, this liner is suitable for high speed laser production presses and copiers as well as most desktop models. It is also suitable for certain offset

applications.

Typical Value

Basis Weight: 58 #/3000 ft² Caliper: 3.8 mils

Tensile MD/CD: 37 / 20 #/inch Tear MD/CD: 50 / 65 grams

Opacity: 85%

Total Product Caliper: 9.1 mils For application recommendations call 877-210-5104 For samples or other questions please call your Sales Representative.

Product Basis Weight Per MMSI: 260.63 #

Shelf Life: 12 month(s) when stored at 72° F, 50% RH

Important Notice

These are typical values and should not be considered a specification. Adhesive properties were tested with a film facestock unless denoted with an asterisk(*).

All trademarks are the property of their respective owners.

All information, recommendations for use, product designations, and descriptive materials about Spinnaker Pressure Sensitive Products, LLC products are believed to be reliable, but the furnishing of such information, recommendations for use, product designations, and descriptive material is for informational purposes only and does not constitute a warranty of any kind by Spinnaker Pressure Sensitive Products, LLC. Because of the variety of possible applications for Spinnaker's products and the continuing development of new applications, all Spinnaker Pressure Sensitive Products, LLC products are sold with the understanding that each purchaser will independently determine the suitability of any product for the purchaser's intended application, converting, and print processes. Spinnaker Pressure Sensitive Products, LLC will review, and may modify the information contained in this document from time to time and customers should ensure they have the most recent information.

Last Revision: 08/26/2024